RIH – PEDI KNEE CT SIEMENS DEFINITION AS20 PROTOCOL

Indication: fracture, dislocation, osteomyelitis, bone injury, bone tumor.

Position/Landmark	Supine, feet first					
Topogram Direction	Zero Appropriately					
Topogram Direction	Craniocaudal					
Respiratory Phase	Any					
Scan Type	Helical					
Ref kV/Ref mAs/Rotation time (sec)	Care kV 100 / Care Dose4D 65 / 1 sec					
Pitch / Speed (mm/rotation)	.8:1, 10.00mm					
Safire Strength / Dose Optimization		3/5				
Detector width x Rows = Beam Collimation	$0.625 \text{mm} \times 20 = 12.5 \text{mm}$					
Average Tube Output	ctdi – 2.0mGy					
		dlp – 90mGy.cm				
Helical Set		body	thickness/		recon	
Slice Thickness/ Spacing	reco	n part	spacing	algorithm	destination .	
Algorithm	1	axial soft knee	3mm x 3mm	I40s medium	pacs	
Recon Destination	2	axial bony knee	3mm x 3mm	I70h very sharp	pacs	
	3	coronal knee	3mm x 3mm	I70h very sharp	pacs	
	4	sagittal knee	3mm x 3mm	I70h very sharp	pacs	
	5	thin knee	.75mm x .7mm	I70h very sharp	terarecon	
Scan Start / End Locations	det	determined by technologist or radiologist to include the anatomy of interest				
	18cm					
DFOV		decrease appropriately				
IV Contrast Volume / Type / Rate	75mL Iohexol (Omnipaque 350) / 2mL per second					
1 Contract Contract Type (1996)		if needed				
Scan Delay	65 seconds					
	***	77. 1				
2D/3D Technique Used	Workstream 4D mpr of 3mm x 3mm coronal and sagittal knee series (auto-					
	batch off), average mode, auto-transferred to PACS					
Comments: Recon 5 is a thin helical volume of the knee that is archived to the TeraRecon server.						
Images required in PACS	Topog	Topograms, 3mm x 3mm axial knee bone, 3mm x 3mm axial knee standard,				
•		3mm x 3mm sagittal knee, 3mm x 3mm coronal knee, Patient Protocol				